

- Best-in-class optical performance
- Designed for medical and healthcare requirements
- 35% energy savings using LED technology
- 3 year standard warranty



## 2401LM 24-inch Desktop Touch Monitor for Medical and Healthcare Settings

### Overview

The fully featured 2401LM touch monitor offers IntelliTouch® surface acoustic wave (SAW) touchscreen technology which provides stable "drift-free" touch response, outstanding image clarity and full HD resolution, resulting in an accurate touch experience and vivid images. Additionally, the touch monitor is equipped with industry standard connectivity in the form of a combination USB and RS232 touch controller, DVI-D, VGA connectors and built-in audio amp with stereo speakers. The 2401LM is available in medical white or black color.

The 2401LM is compliant with multiple safety and electrical certification standards, including EN 60950-1 and EN 60601-1 for safety and EN 60950-1, EN55022, EN55024, and EN 60601-1 (3rd Edition) for EMC. Equipped with an LED

backlit state-of-the-art LCD panel, the monitor is environmentally friendly with reduced power consumption.

The Elo 2401LM touch monitor is an effective solution for nurse stations, computer-aided therapy, electronic medical record keeping, paperless charting, patient self-check-in, as well as non-medical applications that benefit from DVI-D input, speakers and a pristine full HD image display.

Having been "designed for touch", the 2401LM features a stable stand with tilting functionality which can be removed for VESA mounting; cable management and cable fastening features to prevent accidental disconnection; OSD controls with lockout capability; and an IPx1 drip-resistant housing

### Benefits:

#### Reliable

- Pure-glass touchscreen for superior image quality and drift-free performance
- Compliant with multiple safety and electrical certifications recognized by public health authorities
- Elo controlled design with long product life cycle and availability cycle

### Applications:

- Nurse stations
- Patient self-check in
- Paperless charting
- Electronic record keeping

### About Elo

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touch monitors, and all-in-one touch computers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.



## 2401LM 24-inch Desktop Touchmonitor

Specifications	
Model	2401LM
Color	Black and white
Active Display Area	531.4 x 298.9 mm / 20.9 x 11.7 inches
Monitor Dimensions (without stand)	606 x 373 x 61 mm / 23.9 x 14.6 x 2.4 inches
LCD Technology	Active matrix TFT LCD
Diagonal Size	24.0"
Aspect Ratio	16:9
Native Resolution	1920 x 1080 at 60 Hz
Preset Video Modes	1920 x 1080 60Hz ( Native ), 640 x 350 70Hz, 720 x 400 70Hz, 640 x 480 60, 72 & 75Hz, 800 x 600 56, 60, 72 & 75Hz, 832 x 624 75Hz, 1024 x 768 60, 70 & 75Hz, 1280 x 800 60Hz, 1280 x 960 60Hz, 1280 x 1024 60Hz & 75Hz, 1360 x 768 60Hz, 1366 x 768 60Hz, 1440 x 900 60Hz, 1600 x 1200 60Hz, 1680 x 1050 60Hz
Number of Colors	16,7 million
Brightness (typical)	LCD Panel: 300 nits; IntelliTouch: 270 nits
Response Time (Tr+tf) (typical)	25ms
Viewing Angle (typical)	Horizontal: 178 °; Vertical: 178 °
Contrast Ratio (typical)	3000:1
Video	Input connector: 3.5mm TRS jack Input signal range: 0.5Vrms maximum stereo signal Internal Speakers output: Two 1W speakers
Audio	Input connector: 3.5mm TRS jack Input signal range: 0.5Vrms maximum stereo signal Internal Speakers output: Two 1W speakers
Power	Input voltage AC Adaptor: 100-240 VAC, 50/60Hz Input voltage Monitor DC: 12 VDC +/- 0.5V Input connector AC Adaptor: IEC 60320 C14 Input connector Monitor DC: 4 pin Mini DIN Power Consumption (Typical): ON: 32W
Weight	Unpackaged: 8,8 kg (19,4 lb); Packaged: 13,2 kg (29 lb)
Shipping Dimensions	711 x 508 x 267 mm / 28 x 20 x 10.5 inches
Mounting Options	100 mm VESA rear-mount
On-Screen Display (OSD) Controls	<b>Controls (bottom):</b> menu, up, down, select, power <b>Settings:</b> contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, volume, sharpness, OSD H/V POS, OSDTime <b>Languages:</b> English, German, Spanish, Japanese, French, Italian, Chinese, Polish, Swedish <b>Lockouts:</b> power, user controls
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 10% to 90%
Regulatory Approvals and Declarations	UL/cUL, CE EN/IEC 60601-1 3rd ed., FCC Class B, VCCI, C-Tick, KC, GOST, BSMI, CCC, China RoHS, IPX1 Elo Declarations: RoHS, WEEE, CE
Touch Interface	Serial (RS232) and USB
Warranty	3 years standard
MTBF	50,000 hours demonstrated

### Ordering Information

Model	Part Number	Technology	Surface Treatment	Color	Availability
2401LM	E263686	IntelliTouch	Anti-glare	White	Worldwide
	E000140	IntelliTouch	Anti-glare	Black	Worldwide

### Optional Peripherals

Model	Part
Repl. medical grade power adapter	E000648
IntelliTouch Stylus Pen	D82064-000

**Medical and Healthcare Application Disclaimer:** It is the sole responsibility of any person intending to commercialize, market or use any of Elo Touch Solutions, Inc. or its family of companies ("Elo") products for medical or healthcare applications to ensure that such product is adequate and appropriate for the person's intended use and complies with all applicable laws, regulations, codes and standards including but not limited to the European Union Medical Device Directive, United States Federal Food, Drug, and Cosmetic Act, regulations of the United States Food and Drug Administration (FDA), and other similar legislation in jurisdictions around the world, and for obtaining and maintaining any required regulatory approvals including but not limited to any required market clearances. Elo has not sought nor received any rulings from the FDA or any other federal, state, or local government agency or notified body as to the safety, effectiveness or appropriateness of its product for such applications. Persons intending to evaluate or use Elo's product for medical or healthcare purposes must rely on their own medical and legal judgment without any representation on the part of Elo.

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

#### North America

Elo Touch Solutions  
1033 McCarthy Boulevard  
Milpitas, CA 95035

#### 800-ELO-TOUCH

Tel +1 408 597 8000  
Fax +1 408 597 8050  
customerservice@elotouch.com

#### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
elosales@elotouch.com

#### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

#### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2013 Elo Touch Solutions, Inc. All rights reserved. DS000082, rev A 10/13





# multisystems

Η multisystems διανέμει και υποστηρίζει τεχνικά, προϊόντα από τους μεγαλύτερους οίκους κατασκευής σε Barcode scanners, εκτυπωτές ετικετών, φορητά τερματικά, λύσεις πλαστικών καρτών τύπου πιστωτικής καθώς και συστήματα λιανικής πώλησης όπως συστήματα Point of sale, ταμειακές μηχανές και φορολογικούς μηχανισμούς.

Στις εγκαταστάσεις μας στο Αιγάλεω λειτουργεί πλήρως εξοπλισμένο τεχνικό εργαστήριο με άρτια καταρτισμένους μηχανικούς που μπορούν να δώσουν λύσεις ακόμα και στις πιο δύσκολες μηχανογραφικές προκλήσεις του χώρου της βιομηχανίας, της εφοδιαστικής αλυσίδας και της λιανικής.

Σας εξυπηρετούμε έναν – έναν προσωπικά προσφέροντας σας τον προσωπικό σας τεχνικό σύμβουλο ο οποίος γνωρίζει τις ανάγκες και τις ιδιαιτερότητες της επιχείρησής σας ενώ σας εξυπηρετεί σε όλη την πορεία της συνεργασίας σας μαζί μας ή εξέλιξης του έργου σας. Είμαστε δίπλα σας να σας συμβουλέψουμε να επιλέξετε τον σωστό εξοπλισμό μέσα από μια ευρύτατη γκάμα 12.000 προϊόντων τεχνολογίας για όλες τις ανάγκες από τα πιο επώνυμα εργοστάσια της παγκόσμιας αγοράς.

Για την καλύτερη εξυπηρέτησή σας έχουμε διαχωρίσει τα εμπορικά και τα τεχνικά μας τμήματα σε 6 διακριτές ενότητες τις οποίες μπορείτε να δείτε στον πίνακα που ακολουθεί προκειμένου να σας εξυπηρετούμε γρήγορα και αποτελεσματικά. Για οτιδήποτε χρειαστείτε μην διστάσετε να επικοινωνήσετε μαζί μας στο **211 780 1000**, θα χαρούμε να σας εξυπηρετήσουμε.

Η multisystems διαθέτει και υποστηρίζει



### Barcode scanners

Ενσύρματα | Ασύρματα | 2D Imagers | Bluetooth IOS / Android | Λιανικής



### Εκτυπωτές ετικετών & αναλώσιμα

Επιτραπέζιοι | Βιομηχανικοί | Έγχρωμοι | Ετικέτες | Μελανοταινίες



### Φορητά τερματικά

Φορητά τερματικά | Βιομηχανικά Tablets | Τερματικά αυτοκινήτου / Κλαρκ



### Συστήματα λιανικής πώλησης Point of sale

Συστήματα POS | Touchscreen οθόνες | Θερμικοί εκτυπωτές



### Λύσεις πλαστικών καρτών

Εκτυπωτές πλαστικών καρτών | Αναλώσιμα | Πλαστικές κάρτες PVC



### Φορολογικά προϊόντα

Ταμειακές μηχανές | Φορολογικοί μηχανισμοί | Φορολογικοί εκτυπωτές

Συνεργαζόμενοι οίκοι

**DATALOGIC**

**ZEBRA**

**hp Gold Partner**

**Honeywell**

**PERFORMANCE PARTNER PROGRAM SILVER LEVEL**

**EPSON AUTHORISED PARTNER 2015**

**Intermec®**

**do™**

**datamax • o'neil**

**elo TOUCH SOLUTIONS**

**socket® mobile**

**evolis card printers**

**AVATO**

**CITIZEN Micro HumanTech**



multisystems

ACR Electronics ΕΠΕ

Λεωφ. Θηβών 339, 122 43, Αιγάλεω

<http://www.multisystems.gr> | [info@multisystems.gr](mailto:info@multisystems.gr)

Tel. 211 780 1000 Fax 211 780 2000