

- Rugged & Connected
- Windows / Intel Architecture
- Integrated MSR, Barcode Reader, Smart Card Reader
- Docking Station Accessory



## Elo Tablet

### Overview

The Elo® Tablet is designed to help retailers enhance their customer experience and drive sales efficiency through a point-of-service (POS) and point-of-information (POI) platform that is portable, intuitive, reliable and secure. Millions of real-life retail installations all over the world have helped Elo develop unique insight for this next generation of our touch computing innovation.

Running Microsoft® Windows® and featuring an Intel® Atom™ processor with solid-state drive, the tablet has been purpose-built to support leading point-of-sale software environments

### Professional Touch, Built for Retail

With a broad product portfolio, proven history of quality & reliability, and strong industry partnerships – Elo can help redefine how stores attract and retain customers. Elo's retail tablet directly answers the requirements of a hardened store system for mobile POS, line busting, and inventory management. The Elo tablet delivers all the functionality for native POS transactions and shopper assist.

For over 40 years, with installations at more than twenty million locations around the world, Elo Touch Solutions delivers dependable retail-hardened store systems. Market leaders across

and the mobile POS (mPOS) initiatives embraced by leading retailers. This is a tablet with all the centralized management and security capabilities of the Windows environment, in a commercial form factor that reduces theft risk. An integrated magnetic stripe reader, barcode reader, removable battery and wireless printing/networking is housed in a form factor designed to withstand being dropped. An optional accessory docking station provides connectivity to a broad array of peripheral interfaces while also charging the main battery and an auxiliary battery pack simultaneously.

the globe rely on Elo store technology day in and day out to facilitate critical point of sale transactions, enhance brand experiences and drive interactive omnichannel portals. Elo provides the largest portfolio of systems supporting the largest breadth of touch technologies. Rather than requiring the user to adapt to one type of touch, Elo's architecture delivers broad flexibility of acoustic, capacitive, infrared, optical, projected and resistive technology which adapts to a variety of retail environments where mobility, design style, lighting, moisture, gloves, 24/7 reliability, and ease of retail deployment can all be optimized.



## Benefits:

### Reliable

- Ruggedized to survive retail environments
- Centralized security and management
- Quality touch from a trusted retail supplier

### Integrated

- MSR, Barcode Reader, and Smart Card Reader
- Wi-Fi, Bluetooth, NFC and RFID wireless
- Docking station with battery charging location, Ethernet, 3 x USB, and VGA

### Compatible

- Windows / Intel support for your existing applications
- USB connectivity to external peripherals
- Deployable in cloud, thin-client, or client-server environments

### Purpose Built

- Mobile Point-of-Service
- Omnichannel Insight
- Endless Aisle

## About Elo

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touch screen components, touch monitors, and all-in-one touch computers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

## Elo Tablet

Specifications			
Model	ETT10A1 Windows Embedded 7 Standard (E806980) or Without O/S (E489570)		
Screen Size	10.1"		
Processor	Intel Atom N2600 Dual Core 1.6 GHz		
Chipset	Intel NM10		
BIOS	Phoenix		
Memory (RAM)	2GB DDR3 – 1066 MHz (not expandable beyond 2GB)		
Storage	32GB MSATA SSD		
USB Ports	1 x USB 2.0 on tablet; 3 x USB 2.0 on Docking Station		
Ethernet Port	1 x LAN RJ45 (10/100Mbps) (when docked in Docking Station)		
Wireless	Wi-Fi (802.11 b/g/n), Bluetooth (4.0), NFCIP-1 Reader/Writer		
Audio Ports	3.5mm audio mic/earphone hidden/protected cover		
Speakers	Internal speaker		
Operating System Options	Windows Embedded 7 Standard (Also licensed for Windows Embedded 8 Standard)		
Languages	English (default), French, German, Italian, Spanish, Simplified Chinese, Traditional Chinese		
Display	1366x768 LCD on tablet; VGA DB15 output via Docking Station		
Aspect Ratio	16:9 (wide)		
Active Display Area	222 mm x 125 mm		
Native (optimal) Resolution	1366 x 768		
Brightness (typical)	LCD Panel: 380 nits With Touchscreen: 335 nits		
Contrast Ratio (typical)	800:1		
Display Response Time (typical)	25ms		
Touch Technology	PCAP (Projected Capacitive) Multi Touch (4 touch)		
Power Adapter	AC 120/220V (50/60 Hz), 36W		
Typical Power Consumption (without peripherals)	7W - estimated battery run time up to 7 hours		
Maximum Dimensions (W x H x D)	Tablet : 11.52" x 0.79" x 8.17"	Dock : 11.5" x 7.1" x 7.8"	
Shipping Box Dimensions (W x H x D)	Tablet : 15.8" x 4.1" x 12.5"	Docking : 24.2" x 15.3" x 20.3"	
Weight	Tablet : 2.5 lbs	Docking: 2.8 lbs	
Shipping Weight	Tablet: 4.4 lbs	Docking : 4.8 lbs	
Temperature	Operating: 0°C to 40°C	Storage: -20°C to 60°C	
Humidity (non-condensing)	Operating: 20% to 80%	Storage: 5% to 95%	
Regulatory approvals and declarations	UL/cUL FCC	CE CB	UNDOT ROHS
REACH			
Mounting Options	VESA mount via optional accessory bracket (E624438)		
MTBF	50,000 hours demonstrated		
Sealing	IP54		
Rugged	Tested to MIL-STD-810G drop spec at 1 meter*		
Power Cables	North American and European power cables included		
Other Functions	Integrated Magnetic Stripe Reader (MSR) Internal/ integrated barcode reader (via rear facing auto focus camera)	Internal/ integrated Smart Card Reader Internal Webcam (Front facing AF Camera)	
Optional Accessories	Docking Station (E518363) VESA Bracket (E624438) Stylus (E761200) Additional Battery (E840851)	Replacement Dock Cover (E108413) Replacement Hand Strap (E697779) Replacement Power Supply (E452058)	
Warranty	18 months standard warranty Optional extended warranty available for additional 18 months		
Optional Product Coverage	Advance Unit Replacement program Extended Warranty program		

\* Test results do not guarantee future performance under these test conditions.

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

Elo Touch Solutions  
1033 McCarthy Boulevard  
Milpitas, CA 95035

### 800-ELO-TOUCH

Tel +1 408 597 8000  
Fax +1 408 597 8001  
customerservice@elotouch.com

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
elosales@elotouch.com

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2015 Elo Touch Solutions, Inc. All rights reserved. DS000078, rev F 03/15





# multisystems

Η multisystems διανέμει και υποστηρίζει τεχνικά, προϊόντα από τους μεγαλύτερους οίκους κατασκευής σε Barcode scanners, εκτυπωτές ετικετών, φορητά τερματικά, λύσεις πλαστικών καρτών τύπου πιστωτικής καθώς και συστήματα λιανικής πώλησης όπως συστήματα Point of sale, ταμειακές μηχανές και φορολογικούς μηχανισμούς.

Στις εγκαταστάσεις μας στο Αιγάλεω λειτουργεί πλήρως εξοπλισμένο τεχνικό εργαστήριο με άρτια καταρτισμένους μηχανικούς που μπορούν να δώσουν λύσεις ακόμα και στις πιο δύσκολες μηχανογραφικές προκλήσεις του χώρου της βιομηχανίας, της εφοδιαστικής αλυσίδας και της λιανικής.

Σας εξυπηρετούμε έναν – έναν προσωπικά προσφέροντας σας τον προσωπικό σας τεχνικό σύμβουλο ο οποίος γνωρίζει τις ανάγκες και τις ιδιαιτερότητες της επιχείρησής σας ενώ σας εξυπηρετεί σε όλη την πορεία της συνεργασίας σας μαζί μας ή εξέλιξης του έργου σας. Είμαστε δίπλα σας να σας συμβουλέψουμε να επιλέξετε τον σωστό εξοπλισμό μέσα από μια ευρύτατη γκάμα 12.000 προϊόντων τεχνολογίας για όλες τις ανάγκες από τα πιο επώνυμα εργοστάσια της παγκόσμιας αγοράς.

Για την καλύτερη εξυπηρέτησή σας έχουμε διαχωρίσει τα εμπορικά και τα τεχνικά μας τμήματα σε 6 διακριτές ενότητες τις οποίες μπορείτε να δείτε στον πίνακα που ακολουθεί προκειμένου να σας εξυπηρετούμε γρήγορα και αποτελεσματικά. Για οτιδήποτε χρειαστείτε μην διστάσετε να επικοινωνήσετε μαζί μας στο **211 780 1000**, θα χαρούμε να σας εξυπηρετήσουμε.

Η multisystems διαθέτει και υποστηρίζει



### Barcode scanners

Ενσύρματα | Ασύρματα | 2D Imagers | Bluetooth IOS / Android | Λιανικής



### Εκτυπωτές ετικετών & αναλώσιμα

Επιτραπέζιοι | Βιομηχανικοί | Έγχρωμοι | Ετικέτες | Μελανοταινίες



### Φορητά τερματικά

Φορητά τερματικά | Βιομηχανικά Tablets | Τερματικά αυτοκινήτου / Κλαρκ



### Συστήματα λιανικής πώλησης Point of sale

Συστήματα POS | Touchscreen οθόνες | Θερμικοί εκτυπωτές



### Λύσεις πλαστικών καρτών

Εκτυπωτές πλαστικών καρτών | Αναλώσιμα | Πλαστικές κάρτες PVC



### Φορολογικά προϊόντα

Ταμειακές μηχανές | Φορολογικοί μηχανισμοί | Φορολογικοί εκτυπωτές

Συνεργαζόμενοι οίκοι

**DATALOGIC**

**ZEBRA**

**hp Gold Partner**

**Honeywell**

**PERFORMANCE PARTNER PROGRAM SILVER LEVEL**

**EPSON AUTHORISED PARTNER 2015**

**Intermec®**

**do™**

**datamax • o'neil**

**elo TOUCH SOLUTIONS**

**socket® mobile**

**evolis card printers**

**AVATO**

**CITIZEN Micro HumanTech**



multisystems

ACR Electronics ΕΠΕ

Λεωφ. Θηβών 339, 122 43, Αιγάλεω

<http://www.multisystems.gr> | [info@multisystems.gr](mailto:info@multisystems.gr)

Tel. 211 780 1000 Fax 211 780 2000