

Zebra® 105SL*Plus*™ Printer



SEE MORE. DO MORE.



Economical, dependable, high-performance printing

Zebra's 105SL*Plus* printer provides economical, dependable, high-performance printing. This rugged printer is built for continuous operation, with exactly the features needed for fast, reliable and cost-effective printing in your manufacturing and warehousing environments.

Zebra created the 105SL*Plus* printer with ease of use in mind. The icon-based, multilingual graphical LCD user interface is intuitive to operate, minimising user training and making the printer ideal for a multitude of languages and global applications. The simplified ribbon-loading process minimises downtime.

The 105SL*Plus* printer offers durable all-metal construction and a robust print mechanism to withstand the toughest environments.

The 105SL*Plus* printer leverages Zebra's proven electronics platform to offer increased speed for high-volume applications – and increased storage of formats, fonts and graphics. The print quality is outstanding, with E³™ technology that also extends the life of the printhead.

The 105SL*Plus* printer is designed to easily fit into existing operations. Multiple standard connectivity options including parallel, serial, USB and Ethernet, coupled with full backwards compatibility, make integration fast and simple. For added connectivity, choose the optional ZebraNet™ b/g Print Server for wireless support.

Ideal for:

- **Manufacturing**
 - Product identification labels
 - Packaging labels
 - Receiving/put-away labelling
 - Work-in-process
- **Transportation & Logistics**
 - Order picking/packing
 - Shipping/receiving
 - Cross-docking
 - Compliance labelling
- **Retail**
 - Shipping
 - Returns
- **Government**
 - Asset-tracking
 - Compliance labelling

SPECIFICATIONS AT A GLANCE*

ZEBRA 105SLPlus PRINTERS

Printer name

105SLPlus

Standard features

- Full-function front panel and large multilingual backlit LCD display with user-programmable password protection
- Thin-film printhead with Element Energy Equalizer™ (E3) for superior print quality
- 8MB flash memory, including 2MB user-available non-volatile memory storage for downloadable objects
- Serial RS-232 and bi-directional parallel ports with auto-detect
- USB 2.0
- Dual media sensors (transmissive and reflective) selectable through software or front panel
- Internal ZebraNet 10/100 Print Server supports 10Base-T, 100Base-TX and fast Ethernet 10/100 auto-switching networks

Printer specifications

Resolution

- 203dpi/8 dots per mm
- 300dpi/12 dots per mm (optional)

Memory

- Standard: 16MB SDRAM; 8MB flash

Print width

- 102mm/4.0"

Print length

- 203dpi: 3,810mm/105" (with standard memory)
- 300dpi (optional): 2,540mm/100" (with standard memory)

Print speed

- 203dpi: 305mm/12" per second
- 300dpi: 254mm/10" per second

Media sensors

- Black mark and gap media sensing using fixed centre-position sensors; label-present sensor for issuing labels one at a time

Media specifications

- Media types: continuous, die-cut, or black mark, notch
- Media thickness (label and liner): 0.076mm/0.003" to 0.305mm/0.012"
- Maximum media roll size: 203mm/8.0" O.D. on a 76mm/3" I.D. core
- Media width (label and liner): 20mm/0.79" to 114mm/4.5"
- Maximum non-continuous label length: 991mm/39"

Ribbon characteristics

- Standard lengths: 450m/1476' or 300m/984'
- Provides 2:1 and 3:1 media-roll-to-ribbon ratios
- Maximum ribbon roll size: 81.3mm/3.2" O.D. on a 25.4mm/1.0" I.D. core
- Ribbon wound coated-side out
- Ribbon width: 20mm/0.79" to 110mm/4.33"

Operating characteristics

Environment

- Operating environment:
Thermal-transfer:
5°C/40°F to 40°C/105°F
Direct-thermal:
0°C/32°F to 40°C/105°F
20% to 85% non-condensing relative humidity
- Storage/Transportation environment:
-40°C/-40°F to 60°C/140°F
5% to 85% non-condensing relative humidity

Electrical

- Universal power supply with power-factor correction 100–240VAC, 47–63Hz

Agency approvals

- IEC 60950-1, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3
- Product markings: cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark (Arg), CCC, GOST-R, BSMI, KCC and UkrSEPRO

Physical characteristics

- Height: 393.7mm/15.5"
- Width: 261.9mm/10.31"
- Depth: 517.5mm/20.38"
- Weight: 22.7kg/50 lb

Options and accessories

- Cutter and catch tray
- Media rewind spindle: internal finished-roll rewind or passive-peel with liner take-up spindle
- 64MB On-Board Linear Flash Memory (factory-installed only)
- Scalable and international fonts

ZebraLink™ Solutions

Software

- ZebraDesigner™ Pro
- ZebraDesigner for myXML
- ZebraNet Bridge Enterprise
- ZebraDesigner for mySAP™
- ZebraDesigner for XML
- ZebraNet Utilities v 7.0

Optional connectivity

- ZebraNet b/g Print Server (internal)

Firmware

- ZPL II®
- Zebra Global Printing Solution
- Web View & Alert
- ZBI 2.0™ (optional)

Fonts and character sets

- Zebra Global Printing solution including Unicode™
- Swiss 721 font standard
- Bitmap fonts A to H and GS symbols are expandable up to 10 times, height- and width-independent
- Smooth-scalable font Ø (CG Triumvirate™ Bold Condensed) is expandable dot-by-dot, height- and width-independent
- IBM® code page 850 international characters
- Contains UFST® from Monotype Imaging, Inc. Firmware support for downloadable TrueType™ fonts
- Additional fonts available

Graphics features

- Supports user-defined fonts and graphics, including custom logos

Barcode symbologies

- All standard linear and 2D barcodes supported

For optimum print quality and printer performance, use genuine Zebra supplies.



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 Fax: +44 (0)1628 556001 Email: mseurope@zebra.com Web: www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Russia, Spain, Sweden, Turkey
Middle East & Africa: Dubai, South Africa

*Specifications subject to change without notice.

©2013 ZIH Corp. E3, Element Energy Equalizer, ZBI 2.0, ZebraLink and ZebraNet are Zebra trademarks, and Zebra, representation of Zebra Head and ZPL II are registered trademarks of ZIH Corp. All rights reserved. mySAP is the trademark or registered trademark of SAP AP in Germany and in several other countries. Unicode is a trademark of Unicode, Inc. CG Triumvirate and UFST are trademarks of Monotype Imaging, Inc. and may be registered in certain jurisdictions. IBM is a registered trademark of International Business Machines Corporation in the United States, other countries, or both. TrueType is a trademark of Apple Inc. All other trademarks are the property of their respective owners.



multisystems

Η multisystems διανέμει και υποστηρίζει τεχνικά, προϊόντα από τους μεγαλύτερους οίκους κατασκευής σε Barcode scanners, εκτυπωτές ετικετών, φορητά τερματικά, λύσεις πλαστικών καρτών τύπου πιστωτικής καθώς και συστήματα λιανικής πώλησης όπως συστήματα Point of sale, ταμειακές μηχανές και φορολογικούς μηχανισμούς.

Στις εγκαταστάσεις μας στο Αιγάλεω λειτουργεί πλήρως εξοπλισμένο τεχνικό εργαστήριο με άρτια καταρτισμένους μηχανικούς που μπορούν να δώσουν λύσεις ακόμα και στις πιο δύσκολες μηχανογραφικές προκλήσεις του χώρου της βιομηχανίας, της εφοδιαστικής αλυσίδας και της λιανικής.

Σας εξυπηρετούμε έναν – έναν προσωπικά προσφέροντας σας τον προσωπικό σας τεχνικό σύμβουλο ο οποίος γνωρίζει τις ανάγκες και τις ιδιαιτερότητες της επιχείρησής σας ενώ σας εξυπηρετεί σε όλη την πορεία της συνεργασίας σας μαζί μας ή εξέλιξης του έργου σας. Είμαστε δίπλα σας να σας συμβουλέψουμε να επιλέξετε τον σωστό εξοπλισμό μέσα από μια ευρύτατη γκάμα 12.000 προϊόντων τεχνολογίας για όλες τις ανάγκες από τα πιο επώνυμα εργοστάσια της παγκόσμιας αγοράς.

Για την καλύτερη εξυπηρέτησή σας έχουμε διαχωρίσει τα εμπορικά και τα τεχνικά μας τμήματα σε 6 διακριτές ενότητες τις οποίες μπορείτε να δείτε στον πίνακα που ακολουθεί προκειμένου να σας εξυπηρετούμε γρήγορα και αποτελεσματικά. Για οτιδήποτε χρειαστείτε μην διστάσετε να επικοινωνήσετε μαζί μας στο **211 780 1000**, θα χαρούμε να σας εξυπηρετήσουμε.

Η multisystems διαθέτει και υποστηρίζει



Barcode scanners

Ενσύρματα | Ασύρματα | 2D Imagers | Bluetooth IOS / Android | Λιανικής



Εκτυπωτές ετικετών & αναλώσιμα

Επιτραπέζιοι | Βιομηχανικοί | Έγχρωμοι | Ετικέτες | Μελανοταινίες



Φορητά τερματικά

Φορητά τερματικά | Βιομηχανικά Tablets | Τερματικά αυτοκινήτου / Κλαρκ



Συστήματα λιανικής πώλησης Point of sale

Συστήματα POS | Touchscreen οθόνες | Θερμικοί εκτυπωτές



Λύσεις πλαστικών καρτών

Εκτυπωτές πλαστικών καρτών | Αναλώσιμα | Πλαστικές κάρτες PVC



Φορολογικά προϊόντα

Ταμειακές μηχανές | Φορολογικοί μηχανισμοί | Φορολογικοί εκτυπωτές

Συνεργαζόμενοι οίκοι

DATALOGIC

ZEBRA

hp Gold Partner

Honeywell

PERFORMANCE PARTNER PROGRAM SILVER LEVEL

EPSON AUTHORISED PARTNER 2015

Intermec®

do™

datamax • o'neil

elo TOUCH SOLUTIONS

socket® mobile

evolis card printers

AVATO

CITIZEN Micro HumanTech



multisystems

ACR Electronics ΕΠΕ

Λεωφ. Θηβών 339, 122 43, Αιγάλεω

<http://www.multisystems.gr> | info@multisystems.gr

Tel. 211 780 1000 Fax 211 780 2000