

## Product profile

# PB<sub>22/32/50</sub>

## Rugged Mobile Label Printers



- The industry's fastest 2, 3, and 4 inch rugged mobile label printers
- Built rugged to survive real-world industrial and retail environments
- Two to three times faster time-to-first-label than competitive products
- Low cost of development, deployment and support
- Seamless integration with Intermec mobile computers and other mobile devices
- Secure wired and wireless communications options: Bluetooth®, 802.11 b/g, USB, Serial
- Label sensors minimize printing errors and reduce waste
- SmartSystems® remote device management reduces support needs
- Optimized for Intermec media, including linerless label media options

The Intermec rugged mobile label printer family delivers the fastest choice for customers with demanding applications in warehousing, distribution, in-store retail and enterprise asset management. Coupled with Intermec rugged mobile computers and software, the PB22, PB32 and PB50 mobile label printers help companies improve productivity and efficiency while lowering the total cost of ownership.

With ultra-fast print speed and proven two to three times faster time-to-first-label\* than competitive products, these printers deliver measurable improvements in worker productivity and accuracy. Unique design elements, such as the label gap and label take sensors, help maintain productivity while reducing waste.

The PB label printer family is built on a common electrical and mechanical foundation, and integrates closely with Intermec mobile computers and software, including Intermec Terminal Emulation (ITE) and Intermec SmartSystems®. This integrated approach provides significant efficiencies in development, deployment and support, and optimizes speed and performance. Intermec SmartSystems provides remote monitoring and diagnostics to networked devices so problems can be resolved

quickly. Shared accessories across the family add flexibility and reduce spare inventory and costs. Intermec media options, designed specifically for the PB printers, ensure consistently high print quality across a range of applications.

Leveraging the Intermec platform gives companies a solution that can adapt and grow with their needs. As "smart" printers, the rugged PB printers can host stand-alone applications developed through Intermec Fingerprint programming to address custom requirements today or in the future, without the need to upgrade hardware.

The printers' comprehensive options and easy adaptability meet a range of application needs. Drop-in media loading, adjustable media holders, and the flexibility to print either receipts or labels enables workers to easily change tasks without changing equipment. A choice of secure wired and wireless interfaces (802.11 b/g, BT, Serial, USB) allows you to select the one that fits your environment. Multiple carrying options are available, including belt clip, shoulder strap and vehicle mount.

The rugged design of the PB22, PB32 and PB50 printers means performance you can depend on, day after day. Built



\*Based on tests conducted by Intermec Technologies 03-04/09. For a copy of the test data, please contact Intermec Printer Marketing.

to thrive in the same environment as Intermec computers, the printers have a 5 foot multiple drop spec, IP54 seal rating, and forklift-strength shock and vibration specs, minimizing repairs and downtime. When issues do arise, Intermec Medallion Complete service contracts deliver peace-of-mind and insurance against unbudgeted repair costs.

#### Physical Characteristics

##### PB22:

**Width:** 101 mm (4 in)  
**Height:** 176 mm (6.9 in)  
**Depth:** 71 mm (2.8 in)  
**Weight (with battery):** 678 g (23.9oz)

##### PB32:

**Width:** 127 mm (5 in)  
**Height:** 182 mm (7.2 in)  
**Depth:** 81 mm (3.2 in)  
**Weight (with battery):** 828 g (29.2oz)

##### PB50:

**Width:** 160 mm (6.3 in)  
**Height:** 174.5 mm (6.9 in)  
**Depth:** 78.8 mm (3.1 in)  
**Weight (with battery):** 1189 g (42.0 oz)

#### Environment

**Operating temperature:** -15°C to 50°C (5°F to 122°F)  
**Storage temperature:** -30°C to 70°C (-22°F to 158°F)  
**Humidity:** 10 to 90% (non-condensing)  
**Sealing:** IP54 (excludes paper path)  
**Drop spec:** 1.5m (5 ft.) drops to concrete; 26 times including all corners and sides  
**PB22/32:** 2m (6.5 ft) multiple drops to concrete with optional protective case

#### Power

**PB22/32:** 7.4V Li-Ion, 2.3 Ah, rechargeable battery (typical)  
**PB50:** 14.8V Li-Ion, 2.2 Ah, rechargeable battery

#### Memory

**RAM:** 16MB  
**Flash:** 64MB

#### Standard Communications

RS-232 Serial  
USB v.2.0

#### Optional Communications

Bluetooth® (v2.0, Class 1)  
802.11b/g

#### Wireless Security

**Authentication & Encryption Options:** WEP (64 and 128 bit) LEAP; WPA-PSK (TKIP / RC4); WPA2/802.11i-PSK (CCMP / AES);EAP-TLS, -TTLS, -PEAP, -FAST

#### Print Speed and Resolution

4ips (101.6mm/sec)  
203 dpi (8 dots/mm)

#### Print Technology

**Printhead:** Direct thermal

#### Media

**Type:** Labels or receipt media

##### Intermec Media:

**Labels and Tags:** Duratherm II, Duratherm III, Duratherm NIR, Duratherm III IR, Duratherm III Synthetic, Duratherm III Linerless, Duratherm II 5-mil Tag

**Receipts :** Duratherm Receipt II, Duratherm Receipt III

##### Media Width Ranges:

**PB22:** 25.4mm to 55.88mm (1 to 2.2 in)  
**PB32:** 30.48mm to 83.82mm (1.2 to 3.3 in)  
**PB50:** 49mm to 111.5mm (2 to 4.39 in)

**Core ID:** 19mm (0.75 in) standard, 10.16 mm (0.4 in) supported

##### Max OD:

**PB22:** 57.2mm (2.25 in)  
**PB32:** 67.3mm (2.65 in)  
**PB50:** 67.3mm (2.65 in)

#### Software

##### Programming Languages:

IPL, Fingerprint, ZSim (ZPLII Simulation), ESC-P, DSim (DPL), CSim (CPCL)

#### Character Sets

**Standard:** English and Latin

**Optional:** Western European, ASCII, CodePage 850, Central European, Cyrillic, Latin, Greek, Turkish, Hebrew, Arabic, Baltic, Baltic RIM, Vietnamese, Thai, Simplified Chinese, Traditional Chinese, Korean, UTF-8

#### Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos.

#### Barcode Symbolologies

All major 1D and 2D symbolologies are supported.

#### User Interface

LCD and 4 buttons: standby, paper feed, setup, info  
Four audio status indicators: error alert, hardware change alert, button press alert and startup alert.

#### Accessories

Hand strap, shoulder strap, belt clip, protective case, cart mount, vehicle mount, battery pack, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable

#### Safety Approvals

**North America:** UL and cUL Listed, UL 60950-1

**Europe:** D Mark, EN 60950-1; CE marked

**Mexico:** NYCE Certified, NOM 19

**Other Countries:** IEC 60950-1

#### EMC Approvals

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN55022 Class B + EN55024) ; CISPR22

#### Warranty

One year; additional Medallion service packages available

#### North America

##### Corporate Headquarters

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

##### North Latin America

**Headquarters Office**  
Mexico  
Phone: +52 55 52-41-48-00  
Fax: +52 55 52-11-81-21

#### South Latin America

##### Headquarters Office

Brazil  
Phone: +55 11 5502.6770  
Fax: +55 11 5502.6780

##### Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

##### Asia Pacific

**Headquarters Office**  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

#### Internet

www.intermec.com  
Worldwide Locations:  
www.intermec.com/locations

#### Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW:  
00 800 4488 8844  
Toll ROW: +44 134 435 0296

#### OEM Sales

Phone: (425) 348-2762

#### Media Sales

Phone: (513) 874-5882

#### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

  
**SmartSystems™**

Copyright © 2011 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611944-02F 05/11

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.





# multisystems

Η multisystems διανέμει και υποστηρίζει τεχνικά, προϊόντα από τους μεγαλύτερους οίκους κατασκευής σε Barcode scanners, εκτυπωτές ετικετών, φορητά τερματικά, λύσεις πλαστικών καρτών τύπου πιστωτικής καθώς και συστήματα λιανικής πώλησης όπως συστήματα Point of sale, ταμειακές μηχανές και φορολογικούς μηχανισμούς.

Στις εγκαταστάσεις μας στο Αιγάλεω λειτουργεί πλήρως εξοπλισμένο τεχνικό εργαστήριο με άρτια καταρτισμένους μηχανικούς που μπορούν να δώσουν λύσεις ακόμα και στις πιο δύσκολες μηχανογραφικές προκλήσεις του χώρου της βιομηχανίας, της εφοδιαστικής αλυσίδας και της λιανικής.

Σας εξυπηρετούμε έναν – έναν προσωπικά προσφέροντας σας τον προσωπικό σας τεχνικό σύμβουλο ο οποίος γνωρίζει τις ανάγκες και τις ιδιαιτερότητες της επιχείρησής σας ενώ σας εξυπηρετεί σε όλη την πορεία της συνεργασίας σας μαζί μας ή εξέλιξης του έργου σας. Είμαστε δίπλα σας να σας συμβουλέψουμε να επιλέξετε τον σωστό εξοπλισμό μέσα από μια ευρύτατη γκάμα 12.000 προϊόντων τεχνολογίας για όλες τις ανάγκες από τα πιο επώνυμα εργοστάσια της παγκόσμιας αγοράς.

Για την καλύτερη εξυπηρέτησή σας έχουμε διαχωρίσει τα εμπορικά και τα τεχνικά μας τμήματα σε 6 διακριτές ενότητες τις οποίες μπορείτε να δείτε στον πίνακα που ακολουθεί προκειμένου να σας εξυπηρετούμε γρήγορα και αποτελεσματικά. Για οτιδήποτε χρειαστείτε μην διστάσετε να επικοινωνήσετε μαζί μας στο **211 780 1000**, θα χαρούμε να σας εξυπηρετήσουμε.

Η multisystems διαθέτει και υποστηρίζει



### Barcode scanners

Ενσύρματα | Ασύρματα | 2D Imagers | Bluetooth IOS / Android | Λιανικής



### Εκτυπωτές ετικετών & αναλώσιμα

Επιτραπέζιοι | Βιομηχανικοί | Έγχρωμοι | Ετικέτες | Μελανοταινίες



### Φορητά τερματικά

Φορητά τερματικά | Βιομηχανικά Tablets | Τερματικά αυτοκινήτου / Κλαρκ



### Συστήματα λιανικής πώλησης Point of sale

Συστήματα POS | Touchscreen οθόνες | Θερμικοί εκτυπωτές



### Λύσεις πλαστικών καρτών

Εκτυπωτές πλαστικών καρτών | Αναλώσιμα | Πλαστικές κάρτες PVC



### Φορολογικά προϊόντα

Ταμειακές μηχανές | Φορολογικοί μηχανισμοί | Φορολογικοί εκτυπωτές

Συνεργαζόμενοι οίκοι

**DATALOGIC**

**ZEBRA**

**hp Gold Partner**

**Honeywell**

**PERFORMANCE PARTNER PROGRAM SILVER LEVEL**

**EPSON AUTHORISED PARTNER 2015**

**Intermec®**

**do™**

**datamax • o'neil**

**elo TOUCH SOLUTIONS**

**socket® mobile**

**evolis card printers**

**AVATO**

**CITIZEN Micro HumanTech**



multisystems

ACR Electronics ΕΠΕ

Λεωφ. Θηβών 339, 122 43, Αιγάλεω

<http://www.multisystems.gr> | [info@multisystems.gr](mailto:info@multisystems.gr)

Tel. 211 780 1000 Fax 211 780 2000